A Type Aluminium Step Ladder

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS803-5	5	30CM	143CM	7KG	153×42×20CM	1.2MM	150KG	Shrink
SS803-6	6	30CM	170CM	8.4KG	183×44×20CM	1.2MM	150KG	Shrink
SS803-7	7	30CM	200CM	10KG	213×46×20CM	1.2MM	150KG	Shrink
SS803-8	8	30CM	227CM	11.6KG	243×48×20CM	1.2MM	150KG	Shrink
SS803-9	9	30CM	255CM	13.2KG	273×50×20CM	1.2MM	150KG	Shrink
SS803-10	10	30CM	285CM	14.8KG	303×52×20CM	1.2MM	150KG	Shrink
SS803-12	12	30CM	340CM	18.4KG	363×54×20CM	1.4MM	150KG	Shrink
SS803-14	14	30CM	400CM	21.2KG	423×56×20CM	1.4MM	150KG	Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/a-type-aluminium-step-ladder.html
Contact: stevenshawn@ssladders.com