A Type Folding Fiberglass Step Ladder B

English technical sheet | Revision 2026-11-16 | 6 listed models

Item No.	Step	Withstand Voltage	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SSF805-5	5	35KV	30CM	143CM	9.5KG	153×42×20CM	3.0MM	150KG	Cover&Shrink
SSF805-6	6	35KV	30CM	170CM	10.8KG	183×44×20CM	3.0MM	150KG	Cover&Shrink
SSF805-7	7	35KV	30CM	201CM	12.6KG	213×46×20CM	3.0MM	150KG	Cover&Shrink
SSF805-8	8	35KV	30CM	230CM	14.2KG	243×48×20CM	3.0MM	150KG	Cover&Shrink
SSF805-9	9	35KV	30CM	260CM	16KG	273×50×20CM	3.0MM	150KG	Cover&Shrink
SSF805-10	10	35KV	30CM	290CM	18KG	303×52×20CM	3.0MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/a-type-folding-fiberglass-step-ladder-b.html
Contact: stevenshawn@ssladders.com