Aluminium Household Step Ladder

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS802-3	3	28CM	118CM	2.6KG	123×40×6CM	1.2MM	150KG	Shrink
SS802-4	4	28CM	138CM	3KG	151×40×6CM	1.2MM	150KG	Shrink
SS802-5	5	28CM	158CM	3.5KG	180×40×6CM	1.2MM	150KG	Shrink
SS802-6	6	28CM	178CM	3.97KG	210×40×6CM	1.2MM	150KG	Shrink
SS802-7	7	28CM	198CM	4.47KG	240×40×6CM	1.2MM	150KG	Shrink
SS802-8	8	28CM	218CM	4.9KG	270×40×6CM	1.2MM	150KG	Shrink
SS802-9	9	28CM	238CM	5.5KG	300×40×6CM	1.2MM	150KG	Shrink
SS802-10	10	28CM	258CM	6KG	330×40×6CM	1.2MM	150KG	Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/aluminium-household-step-ladder.html
Contact: stevenshawn@ssladders.com