Aluminium I-Section Side Rails Rope Ladder

English technical sheet | Revision 2026-11-16 | 5 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS9804-12A	12×2	30CM	613CM	20.4KG	380×45×14CM	2-5MM	150KG	Cover&Shrink
SS9804-14A	14×2	30CM	733CM	23.5KG	440×45×14CM	2-5MM	150KG	Cover&Shrink
SS9804-16A	16×2	30CM	853CM	26.35KG	500×45×14CM	2-5MM	150KG	Cover&Shrink
SS9804-18A	18×2	30CM	943CM	29.5KG	540×45×14CM	2-5MM	150KG	Cover&Shrink
SS9804-20A	20×2	30CM	1063CM	32KG	600×45×14CM	2-5MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/aluminium-i-section-side-rails-rope-ladder.html
Contact: stevenshawn@ssladders.com