Aluminium Platform Ladder B

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS807B-3	3	30CM	144CM	7.6KG	158×50×13CM	1.2MM	150KG	Cover&Shrink
SS807B-4	4	30CM	174CM	9.2KG	188×52×13CM	1.2MM	150KG	Cover&Shrink
SS807B-5	5	30CM	204CM	10.8KG	218×54×13CM	1.2MM	150KG	Cover&Shrink
SS807B-6	6	30CM	232CM	12.4KG	248×56×13CM	1.2MM	150KG	Cover&Shrink
SS807B-7	7	30CM	262CM	14KG	278×58×13CM	1.2MM	150KG	Cover&Shrink
SS807B-8	8	30CM	292CM	15.6KG	308×60×13CM	1.2MM	150KG	Cover&Shrink
SS807B-9	9	30CM	322CM	17.2KG	338×62×13CM	1.2MM	150KG	Cover&Shrink
SS807B-10	10	30CM	352CM	18.8KG	368×64×13CM	1.2MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/aluminium-platform-ladder-b.html
Contact: stevenshawn@ssladders.com