Aluminium Pole Stick Orchard Step Ladder

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS813-3	3	30CM	109CM	3KG	115×35×20CM	1.2MM	150KG	Shrink
SS813-4	4	30CM	142CM	4.5KG	145×40×25CM	1.2MM	150KG	Shrink
SS813-5	5	30CM	175CM	6KG	175×42×27CM	1.2MM	150KG	Shrink
SS813-6	6	30CM	210CM	7.5KG	205×45×30CM	1.2MM	150KG	Shrink
SS813-7	7	30CM	241CM	9KG	245×48×33CM	1.2MM	150KG	Shrink
SS813-8	8	30CM	274CM	10.5KG	275×50×35CM	1.2MM	150KG	Shrink
SS813-9	9	30CM	307CM	12KG	305×53×37CM	1.2MM	150KG	Shrink
SS813-10	10	30CM	340CM	13.5KG	345×57×42CM	1.2MM	150KG	Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/aluminium-pole-stick-orchard-step-ladder.html
Contact: stevenshawn@ssladders.com