Fiberglass Multipurpose Ladder 80mm

English technical sheet | Revision 2026-11-16 | 5 listed models

Item No.	Step	Withstand Voltage	Pedal Spacing	Straight/A Shape Height	Weight	Packing Size	Thickness	Max Load	Packing
SSF801-370	4×3	35KV	28CM	352/174CM	14.6KG	98×27.5×37CM	3.0MM	150KG	Cover&Shrink
SSF801-475	4×4	35KV	28CM	464/227CM	16.8KG	125×27.5×37CM	3.0MM	150KG	Cover&Shrink
SSF801-580	4×5	35KV	28CM	575/281CM	18.8KG	153×27.5×37CM	3.0MM	150KG	Cover&Shrink
SSF801-700	4×6	35KV	28CM	685/335CM	21KG	181×27.5×37CM	3.0MM	150KG	Cover&Shrink
SSF801-840	4×7	35KV	28CM	795/389CM	23.2KG	209×27.5×37CM	3.0MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/fiberglass-multipurpose-ladder-86mm.html
Contact: stevenshawn@ssladders.com