Fiberglass Platform Ladder with Handrails — SSF811 Series

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Withstand Voltage	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SSF811-3	3	35KV	30CM	173CM	11.5KG	185×60×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-4	4	35KV	30CM	202CM	13.1KG	215×62×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-5	5	35KV	30CM	230CM	16KG	245×64×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-6	6	35KV	30CM	258CM	17.7KG	275×66×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-7	7	35KV	30CM	286CM	19.7KG	305×68×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-8	8	35KV	30CM	315CM	21.4KG	335×70×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-10	10	35KV	30CM	370CM	25.4KG	395×74×14.3CM	3.0MM	150KG	Cover&Shrink
SSF811-12	12	35KV	30CM	428CM	29.6KG	455×78×14.3CM	3.0MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/fiberglass-platform-ladder-with-handrails.html
Contact: stevenshawn@ssladders.com