Fiberglass Single Side Step Ladder with Side Tray

English technical sheet | Revision 2026-11-16 | 8 listed models

Item No.	Step	Withstand Voltage	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SSFW802-3	2	35KV	30CM	87CM	4.8KG	96×39×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-4	3	35KV	30CM	116CM	5.8KG	126×41×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-5	4	35KV	30CM	145CM	7.4KG	156×43×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-6	5	35KV	30CM	172CM	8.2KG	186×45×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-7	6	35KV	30CM	203CM	9.4KG	216×47×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-8	7	35KV	30CM	233CM	10.6KG	246×49×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-9	8	35KV	30CM	261CM	12KG	276×51×13CM	3.0MM	150KG	Cover&Shrink
SSFW802-10	9	35KV	30CM	290CM	13.4KG	306×53×13CM	3.0MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/fiberglass-single-side-step-ladder-with-side-tray.html
Contact: stevenshawn@ssladders.com