Heavy 75mm Frame Three Section Aluminium Rope Ladder

English technical sheet | Revision 2026-11-16 | 6 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SSN80675-10	10×3	28CM	690CM	19.2KG	300×41×20CM	2-5MM	150KG	Cover&Shrink
SSN80675-12	12×3	28CM	827CM	22.4KG	355×41×20CM	2-5MM	150KG	Cover&Shrink
SSN80675-14	14×3	28CM	992CM	25.4KG	410×41×20CM	2-5MM	150KG	Cover&Shrink
SSN80675-16	16×3	28CM	1172CM	28.7KG	468×41×20CM	2-5MM	150KG	Cover&Shrink
SSN80675-18	18×3	28CM	1284CM	30.9KG	526×41×20CM	2-5MM	150KG	Cover&Shrink
SSN80675-20	20×3	28CM	1457CM	34KG	582×41×20CM	2-5MM	150KG	Cover&Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/heavy-75mm-frame-three-section-aluminium-rope-ladder.html
Contact: stevenshawn@ssladders.com