Three Section Smooth Frame Aluminium Ladder 1.2mm

English technical sheet | Revision 2026-11-16 | 10 listed models

Item No.	Step	Pedal Spacing	Open Height	Weight	Packing Size	Thickness	Max Load	Packing
SS806-6	6×3	28CM	278CM	8.4KG	170×45×16.5CM	1.2MM	150KG	Shrink
SS806-7	7×3	28CM	353CM	9.2KG	198×45×16.5CM	1.2MM	150KG	Shrink
SS806-8	8×3	28CM	428CM	10KG	226×45×16.5CM	1.2MM	150KG	Shrink
SS806-9	9×3	28CM	503CM	10.8KG	254×45×16.5CM	1.2MM	150KG	Shrink
SS806-10	10×3	28CM	578CM	11.6KG	282×45×16.5CM	1.2MM	150KG	Shrink
SS806-11	11×3	28CM	655CM	12.2KG	310×45×16.5CM	1.2MM	150KG	Shrink
SS806-12	12×3	28CM	731CM	13.4KG	338×45×16.5CM	1.2MM	150KG	Shrink
SS806-13	13×3	28CM	756CM	14.4KG	366×45×16.5CM	1.2MM	150KG	Shrink
SS806-14	14×3	28CM	830CM	15.4KG	394×45×16.5CM	1.2MM	150KG	Shrink
SS806-15	15×3	28CM	905CM	16.2KG	422×45×16.5CM	1.2MM	150KG	Shrink

Scope and ordering notes

Values reproduce the published model table. Weight is listed without a confirmed net/gross basis. Packing dimensions are packaging dimensions, not confirmed folded-product dimensions. Confirm units per pack and the selected model before quotation.

This specification sheet is not a test report, certificate or operating manual. Any listed load or voltage value retains the scope of the source page; request the applicable model and document scope before ordering. Unlisted dimensions are not inferred.

Mixed-model container orders are supported. MOQ: 20 ladders per model, with a minimum total order of 1 × 20-foot container. Confirm the final model mix before quotation.

Production usually takes 30-45 days after sample approval, subject to the selected models, quantities and production schedule. Samples are paid for by the buyer; freight is additional. The sample fee is deducted from the subsequent bulk order. Sample availability and charges are confirmed for the requested model.

Source: https://www.ssladders.com/products/items/three-section-smooth-frame-aluminium-ladder.html
Contact: stevenshawn@ssladders.com